

DIRECT-DRIVE MONO-BLOCK UNIT

- Perfect refrigeration unit for medium-sized trucks
- Mono-block condenser and evaporator that occupy no loading space
- High capacity, fast cooling, and less damage on evaporator
- Quick and easy installation
- Digital and multi-functional control panel, easy operation
- Optional hot gas heating and standby

Model		HT-580M	
Cooling	0°C/+38°C	5800W	19790Btu
Capacity	-18°C/+38°C	3150W	10748Btu
Temperature Range		-18°C~+30°C	
Voltage		DC12V/24V	
Defrosting		Hot gas defrosting	
Evap. Air Volume		2800m³/h	
Refrigerant & Volume		R404a/2.3kg	
Compressor		QP16/QP21	
Condenser	Coils	Parallel flow	
	Fan Qty.	3Pcs	
Evaporator	Coils	Copper tube and fin	
	Fan Qty.	3Pcs	
Dimension		1610*660*705mm	
Weight		96.5kg	
Recommended Box Size		22-30m³	



HT-580M



Notes: 1. The recommended box sizes are presented for reference only, the actual applicable sizes are subject to the box insulation performance(K-value $\leq$ 0.32W/M²°C), ambient temperature, and goods to be delivered, etc.
2. Products specifications and appearance are subject to change without priority notice.

DIRECT-DRIVE REFRIGERATION UNIT

- Great performance for large-sized trucks
- Durable fiberglass shell, extra-slim 4 fans evaporator with large airflow
- High capacity, fast cooling and low failure rate
- Quick and easy installation
- Digital and multi-functional control panel, easy operation
- Optional standby

Model		HT-1000	
Cooling	0°C/+38°C	8500W	29002Btu
Capacity	-18°C/+38°C	5050W	17231Btu
Temperature Range		-18°C~+30°C	
Voltage		DC12V/24V	
Defrosting		Hot gas defrosting	
Heating		Hot gas heating	
Evap. Air Volume		3600m³/h	
Refrigerant & Volume		R404a/3.2kg	
Compressor		QP21/TM32	
Condenser	Coils	Parallel flow	
	Fan Qty.	2Pcs	
	Size	1290*540*465mm	
	Weight	49kg	
Evaporator	Coils	Copper tube and fin	
	Fan Qty.	4Pcs	
	Size	1380*630*250mm	
	Weight	39kg	
Recommended Box Size		40-50m³	



HT-1000



Notes: 1. The recommended box sizes are presented for reference only, the actual applicable sizes are subject to the box insulation performance(K-value $\leq$ 0.32W/M²°C), ambient temperature, and goods to be delivered, etc.
2. Products specifications and appearance are subject to change without priority notice.