

NOSE-MOUNTED REFRIGERATION UNIT

- Superior performance for small and medium-sized trucks
- Durable fiberglass shell and extra-slim evaporator with large airflow
- Big capacity, fast cooling and low failure rate
- Quick and easy installation
- Digital and multi-functional control panel, easy operation
- Optional hot gas heating and standby



Direct-drive

HT-380



HT-480



HT-680



Model		HT-380		HT-480		HT-680	
Cooling	0°C/+38°C	3850W	13136Btu	5100W	17401Btu	6000W	20472Btu
Capacity	-18°C/+38°C	2150W	7336Btu	2850W	9724Btu	3250W	11089Btu
Temperature Range		-18°C~+30°C		-18°C~+30°C		-18°C~+30°C	
Voltage		DC12V/24V		DC12V/24V		DC12V/24V	
Defrosting		Hot gas defrosting		Hot gas defrosting		Hot gas defrosting	
Evap. Air Volume		1750m³/h		2600m³/h		2600m³/h	
Refrigerant & Volume		R404a/1.4kg		R404a/1.7kg		R404a/2.2kg	
Compressor		Carrier QP16, 163cc/r		Carrier QP16, 163cc/r		Carrier QP16, 163cc/r	
Condenser	Coils	Parallel flow		Parallel flow		Parallel flow	
	Fan Qty.	2Pcs		2Pcs		2Pcs	
	Size	1080*470*320mm		1200*580*390mm		1200*580*390mm	
	Weight	28.5kg		36.5kg		39kg	
Evaporator	Coils	Copper tube and fin		Copper tube and fin		Copper tube and fin	
	Fan Qty.	2Pcs		3Pcs		3Pcs	
	Size	980*570*210mm		1270*790*200mm		1270*790*200mm	
	Weight	20kg		25kg		25kg	
Recommended Box Size		16-22m³		18-25m³		25-35m³	

Notes: 1. The recommended box sizes are presented for reference only, the actual applicable sizes are subject to the box insulation performance(K-value≤0.32W/M²°C), ambient temperature, and goods to be delivered, etc.
2. Products specifications and appearance are subject to change without priority notice.