

NOSE-MOUNTED REFRIGERATION UNIT

- Competitive performance for medium-sized trucks
- Durable fiberglass condenser, al-alloy evaporator with large airflow
- High capacity, fast cooling and low failure rate
- Quick and easy installation
- Digital and multi-functional control panel, easy operation
- Optional hot gas heating and standby



Direct-drive

HT-550



HT-750



Model		HT-550		HT-750	
Cooling	0°C/+38°C	5800W	19790Btu	7450W	25419Btu
Capacity	-18°C/+38°C	3150W	10748Btu	3650W	12454Btu
Temperature Range		-18°C~+30°C		-18°C~+30°C	
Voltage		DC12V/24V		DC12V/24V	
Defrosting		Hot gas defrosting		Hot gas defrosting	
Evap. Air Volume		2600m³/h		3000m³/h	
Refrigerant & Volume		R404a/2.1kg		R404a/3.8kg	
Compressor		Carrier QP16, 163cc/r		Carrier QP21, 215cc/r	
Condenser	Coils	Parallel flow		Parallel flow	
	Fan Qty.	2Pcs		2Pcs	
	Size	1260*600*415mm		1400*530*510mm	
	Weight	36kg		50kg	
Evaporator	Coils	Copper tube and fin		Copper tube and fin	
	Fan Qty.	3Pcs		3Pcs	
	Size	1030*550*300mm		1240*650*355mm	
	Weight	26kg		43kg	
Recommended Box Size		22-30m³		35-45m³	

Notes: 1. The recommended box sizes are presented for reference only, the actual applicable sizes are subject to the box insulation performance(K-values≤0.32W/M²°C), ambient temperature, and goods to be delivered, etc.
2. Products specifications and appearance are subject to change without priority notice.